

PRODUCT NAME

CreteClean Plus with Scar Guard

BENEFITS

• Revolutionary, Cutting Edge Technology

CreteClean *Plus* with Scar Guard is uniquely formulated to clean and condition densified and densified-polished concrete. Proprietary polar technology pulls contaminants out and up from concrete and holds it in suspension, providing maximum cleaning efficiency.

• Green, Environmentally Friendly

CreteClean *Plus* with Scar Guard is a water-based detergent based on green chemistry and contains no VOCs. Because it is so highly concentrated, less product is required for use, and therefore less needs to be purchased, shipped, and stored, greatly reducing its environmental impact.

• Improves Floor Performance

The chemically advanced technology of CreteClean *Plus* with Scar Guard elevates it from a detergent to a performance enhancing cleaning agent. Regular and frequent use of CreteClean *Plus* with Scar Guard can, over time:

- \Rightarrow Help strengthen and harden concrete surfaces,
- \Rightarrow Decrease the visibility of minor scratches and blemishes,
- \Rightarrow Decrease porosity, and
- ⇒ Help maintain the sheen of densified concrete surfaces.

TECHNICAL DATA

Form:	Clear green liquid with fresh scent, weighing 8.5 lbs. per gallon (1.02 kg per liter).
Flashpoint:	Not applicable.
Freezing:	If product freezes, agitate to re-emulsify.
pH:	11.0 - 12.0
Packaging:	55 Gallon (208L) Drums
	5 Gallon (19L) Pails
Storage Life:	Two years.
Dilution	General Cleaning - 1 oz. of CreteClean Plus
Ratio:	per gallon of water (7.8 ml/liter).
	Poultice Method - 4 oz. of CreteClean <i>Plus</i> per gallon of water (31.2 ml/liter).

DIRECTIONS

CreteClean *Plus* is simple and easy to use! First, remove any debris from the area to be cleaned. CreteClean *Plus* can then be applied by wet mop*, automatic scrubber or other means. Remove any excess diluted CreteClean *Plus* and allow the concrete surface to air-dry. For enhanced results on concrete that has been treated with the Ashford Formula or RetroPlate System, periodically burnish or buff the surface with a non-aggressive pad or polishing pad. **To avoid streaking, use only a rayon mop head, and change cleaning solution every* 800 - 1,000 ft² (244 - 305 m²).

FROM THE MAKERS OF

THE ASHFORD FORMULA AND THE RETROPLATE SYSTEM

Poultice Cleaning Procedures for Severe Oil Staining

Remove all loose soil and fine grit. Mop down CreteClean *Plus* diluted at 4 oz./gallon of water (7.8 ml/liter). Agitate the solution to assist the product in penetrating the soil's surface. Cover the wet surface with plastic film and tape down edges. Allow area to remain wet for 10 - 15 minutes or longer if possible. Remove the plastic film and dispose of soiled solution. The procedure may need to be repeated if soil leaches back to the surface as the concrete completely dries out. Note: This procedure is designed for spot removal of significant oil or grease staining. It is not a cleaning procedure.

SPECIAL CONSIDERATIONS

Several applications of CreteClean *Plus* may be needed to remove oil stains from concrete surfaces that have severe oil staining. Additional treatment with an oil emulsifier, such as **CreteStrip**^M*, may be necessary.

Additionally, acids, salts, deicers and other harmful substances should be promptly removed to avoid damage to your floor. A proper, regular, and frequent maintenance program is highly recommended. Making CreteClean *Plus* a part of your maintenance program will ensure superior results.

*CreteStrip" is manufactured exclusively by Curecrete Distribution, Inc. For details, call toll free 800.998.5664.

AVAILABILITY AND COST

CreteClean *Plus* is manufactured exclusively for Curecrete Distribution, Inc. and Advanced Floor Products and is distributed through a worldwide network of regional factory warehouses, area sales representatives and distributors. For pricing information, please call toll free 800.998.5664 or 888.942.3144.

EXTENDED MANUFACTURER WARRANTY

Due to the superior performance achieved by regularly using Crete-Clean *Plus* with Scar Guard, floors treated with the Ashford Formula[™] or RetroPlate System[™] can qualify for an extension of their original Manufacturer Warranty to a Lifetime Warranty. Qualifying conditions apply. Contact Curecrete Distribution, Inc. for more information.

Curecrete Distribution, Inc. warrants this product to be free from any manufacturing defects.

TECHNICAL ASSISTANCE

For technical support and additional cleaning tips and suggestions, please contact the Technical Service Department of Curecrete Distribution, Inc. at 1.800.998.5664.

DISTRIBUTED BY

Curecrete Distribution, Inc.	Phone:	801.489.5663
1203 W. Spring Creek Pl.	Free:	800.998.5664
Springville, UT 84663 USA	Fax:	801.489.3307
Advanced Floor Products	Phone:	801.812.3420
P.O. Box 80533	Free:	888.942.3144
Provo, UT 84605	Fax:	801.812.3400